

SPECIFICATION



LOA		11.40 m	37' 5"
Hull length		10.99 m	36' 1"
LWL		10.40 m	34' 1"
Beam		3.90 m	12' 10"
Draft			
shallow keel		1.62 m	5' 5"
L-keel, medium		2.06 m	6' 9"

Displacement			
shallow keel	approx.	8.66 t	19,092 lbs
L-keel, medium	approx.	8.27 t	18,232 lbs

Engine Diesel			
standard	approx.	27.30 PS	27.30 hp
option	approx.	38.00 PS	38.00 hp

Fuel tank	approx.	160 l	42 gal
Fresh water	approx.	295 l	77 gal


CE Certificate	A - 6 / B - 10		
Design	judel / vrolijk & co		
Interior	HanseYachts Design		

Mast length above WL	approx.	17.60 m	57' 9"
Total sail area	approx.	72.00 m ²	775 sq ft
Main sail			
standard	approx.	43.50 m ²	468 sq ft
furling	approx.	39.00 m ²	420 sq ft
Self-tacking jib	approx.	28.50 m ²	307 sq ft
Genoa	approx.	34.00 m ²	366 sq ft
Crossover	approx.	61.10 m ²	658 sq ft
Gennaker	approx.	93.90 m ²	1,011 sq ft


3888

Hanse 


All measurements/figures are approximate. Errors and omissions excepted. Specification and material can be changed without notice. Valid from 2020.01.01.



Standard



Option



Option

HULL

- 6 hull windows (3 each side)
- GRP hull, isophthalic gelcoat, colour Signal White (RAL 9003), 1st layer vinyl ester resin and solid laminat
- Waterline and cove line, isophthalic gelcoat, colour: Dark Grey (RAL 7043)

KEEL

- L-keel, cast iron, draft: 2.06 m
- GRP rudder with sea-water resistant aluminium shaft and selfaligning bearings

LAYOUT & INTERIOR

- A1: Master cabin with double V-berth and storage space
- B1: Saloon with large L-galley, dining area on stb and sofa on port
 - separate head with shower stall on port (only with XL3001)
- C1: Aft cabin with double berth and storage space on port, utility room on stb (only with XL2001)
- 2-burner gas stove, 12 V fridge approx. 130 l, waste bin, double stainless steel sink with mixing tab
- Interior furniture in high quality marine plywood, satin varnish
- Hanse companionway closing system
- Saloon table, folding with stowage
- Worktop in galley - Black Quartz
- SLS - Scenario light system - touch screen controller and dimmer in saloon

WOOD (FURNITURE, FLOORBOARD)

- Furniture - Mahogany Style, Satin Varnish
- Cupboard fronts in wood colour
- Floorboard - Acacia

UPHOLSTERY

- Mattresses for all berths
- Upholstery - Monte Carlo, colour: Cream

DECK & OUTSIDE EQUIPMENT

- GRP deck with antislip surface, isophthalic gelcoat, colour: Signal White (RAL 9003), 1st layer vinyl ester resin with balsa sandwich core. 1 cockpit locker on stb, stern locker on port and stb, stowage for running rigging at helm position, anchor locker at bow.

- Teak on cockpit benches
- Twin wheel steering system with emergency tiller
- 2 stainless steel steering wheels with leather cover
- Pulpit and pushpit, stainless steel
- Railing, incl. stanchions and stainless steel wire
- Covered halyards and control lines lead to cockpit helm position, organizers and jammers, 4 mooring cleats, handrail on coach roof, bow anchor fitting with teakstep
- 2 LEWMAR 40 ST EVO manual halyard winches
- Swimming ladder
- Anchor and forestay fitting
- Self tacking jib system
- Mainsheet system
- 3 deck hatches - openable, anchor locker hatch, stowage on coach roof with acrylic glass hatch
- Coach roof side windows with openable portlight on ps
- 6 deck coach roof windows with openable portlight in bathroom, glass next to companionway, glass in saloon and master cabin, 2 portlights in cockpit side for aft-cabins

RIG & SAILS

- Rig, anodized aluminium, deck stepped, with kicker, standing and running rigging and 2 reefs
- ELVSTRÖM Dacron sails - full battened, main and jib

NAVIGATION & INSTRUMENTS

- Illuminated compass
- Navigation lights - LED

PROPULSION

- Fuel tank, approx. 160 l
- Engine (Diesel, approx. 29 hp) - saildrive, 2-blade fix propeller

EQUIPMENT

- 12 V and 230 V electric system with main panels and 230 V shore power and sockets.
- AGM battery set, capacity: 1x 90 Ah + 1x 160 Ah AGM
- Country Version: EU / AUS
- Battery charger 35 A
- Manual toilet with sea water flush (B layout)
- LPG gas system, stowage for 1 gas bottle

- Blackwater system (appr. 35 l) with deck extraction and seacock for head, electric and manual bilge pump
- Freshwater system with electric pump and 20 l hotwater, heated also by main engine
- Fresh water tank, appr. 295 l

ACCESSORIES

- Mast steps

SHIPPING & TRANSPORT

- CE - Certificate cat. A - 6 / B - 10 (only with XE1001)
- Owners manual
- EC - Type Examination Certificate